

Certificate Of Approval Of A Polyester Resin

Manufacturer	Carlo Riccò & F.lli S.p.A.
Address	Viale Della Vecchia Ferrovia, 8/10, Correggio (RE), 42015, Italy
Product	POLIPLAST
Type	Dicyclopentadiene
Resin	LR 608
Application	Laminating resin
Characteristics	UPR, Hybrid, DCPD, not pre-accelerated
Applicable LR Rules	Lloyd's Register Rules for the Manufacture, Testing and Certification of Materials
Approved Variants	LR 608 HLU15: <i>Thixotropic, pre-accelerated, short gel time, for hand lay-up</i>
	LR 608 HLU25: <i>Thixotropic, pre-accelerated, medium gel time, for hand lay-up</i>
	LR 608 RTM20: <i>Pre-accelerated, medium gel time, for RTM</i>
	LR 608 RTM35: <i>Pre-accelerated, medium gel time, for RTM</i>
	LR 608 INF40: <i>Pre-accelerated, medium gel time, for infusion</i>

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Mayur Jogia

Lead Specialist - Non-Metallics to Lloyd's Register EMEA
A member of the Lloyd's Register group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Certificate Of Approval Of A Polyester Resin

LR 608 INF40S:
Pre-accelerated, medium gel time, for infusion

LR 608 INF65:
Pre-accelerated, long gel time, for infusion

LR 608 INF65S:
Pre-accelerated, long gel time, for infusion

M 608 M11:
Pre-accelerated, long gel time, for infusion

This certificate is issued to the manufacturer named above. The resin described has been examined in accordance with the requirements of Lloyd's Register and is approved for use in constructions built under Lloyd's Register survey.

This approval is subject to Lloyd's Register being informed of any changes in or modifications to the resin being used in accordance with the manufacturer's instructions and the relevant requirements of Lloyd's Registers Rules and Regulations.